

Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

 <p>UKAS CALIBRATION</p> <p>0338</p> <p>Accredited to ISO/IEC 17025:2017</p>	Department for the Economy (DfE) Trading Standards	
	Issue No: 020	Issue date: 23 February 2023
Department for the Economy Northern Ireland Trading Standards Service 176 Newtownbreda Road Belfast Northern Ireland BT8 6QS	Contact: Ms J Gough Tel: +44 (0) 2890253905 Fax: +44 (0) 2890253953 E-Mail: calibration@economy-ni.gov.uk Website: www.economy-ni.gov.uk	
Calibration performed at the above address only		

Calibration and Measurement Capability (CMC)

Measured Quantity Instrument or Gauge	Range	Expanded Measurement Uncertainty ($k = 2$)	Remarks
MASS	Nominal value (g)	(mg)	NOTES
	25 000	75	1 Intermediate values can be calibrated with an uncertainty interpolated from the next higher and lower values in the table above. 2 Calibration can be given in other units as required. 3 calibration by comparison using Borda's method of substitution.
	20 000	20	
	10 000	10	
	5 000	5.0	
	2 000	2.0	
	1 000	1.0	
	500	0.50	
	200	0.20	
	100	0.10	
	50	0.060	
	20	0.050	
	10	0.040	
	5	0.030	
	2	0.024	
	1	0.020	
	0.5	0.016	
	0.2	0.012	
	0.1	0.010	
	0.05	0.0080	
	0.02	0.0060	
	0.01	0.0050	
	0.005	0.0040	
	0.002	0.0040	
	0.001	0.0040	
END			



0338

Accredited to

ISO/IEC 17025:2017

Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Department for the Economy (DfE) Trading Standards

Issue No: 020 Issue date: 23 February 2023

Calibration performed at main address only

Appendix - Calibration and Measurement Capabilities

Introduction

The definitive statement of the accreditation status of a calibration laboratory is the Accreditation Certificate and the associated Schedule of Accreditation. This Schedule of Accreditation is a critical document, as it defines the measurement capabilities, ranges and boundaries of the calibration activities for which the organisation holds accreditation.

Calibration and Measurement Capabilities (CMCs)

The capabilities provided by accredited calibration laboratories are described by the Calibration and Measurement Capability (CMC), which expresses the lowest measurement uncertainty that can be achieved during a calibration. If a particular device under calibration itself contributes significantly to the uncertainty (for example, if it has limited resolution or exhibits significant non-repeatability) then the uncertainty quoted on a calibration certificate will be increased to account for such factors.

The CMC is normally used to describe the uncertainty that appears in an accredited calibration laboratory's schedule of accreditation and is the uncertainty for which the laboratory has been accredited using the procedure that was the subject of assessment. The measurement uncertainty is calculated according to the procedures given in the GUM and is normally stated as an expanded uncertainty at a coverage probability of 95 %, which usually requires the use of a coverage factor of $k = 2$. An accredited laboratory is not permitted to quote an uncertainty that is smaller than the published measurement uncertainty in certificates issued under its accreditation.

Expression of CMCs - symbols and units

It should be noted that the percentage symbol (%) represents the number 0.01. In cases where the measurement uncertainty is stated as a percentage, this is to be interpreted as meaning percentage of the measurand.

Thus, for example, a measurement uncertainty of 1.5 % means $1.5 \times 0.01 \times q$, where q is the quantity value.

The notation $Q[a, b]$ stands for the root-sum-square of the terms between brackets: $Q[a, b] = [a^2 + b^2]^{1/2}$